



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 32



PRODUCT DATA SHEET



Radial

E-3

B

225

Technologies



All Steel

Performance



Traction



Cut Resistance



Durability



EARTHMAX SR 32

RADIAL OTR TIRES

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
Ø 29"	29.5 R 29	TL	E-3	**	202 B	CRC	288	765	1980	883	6009	48	25.00/3.5	24.00/3.5
	33.25 R 29	TL	E-3	**	209 B	CRC	346	845	2080	915	6250	54	27.00/3.5	26.00/3.5
Ø 35"	37.25 R 35	TL	E-3	**	218 B	CRC	453	963	2381	1062	7229	59	31.00/4.0	-
Ø 39"	40.5/75 R 39	TL	E-3	**	225 B	CRC	505	985	2610	1164	7924	59	32.00/4.5	-
	40.5/75 R 39	TL	E-3	**	225 B	STD	689	985	2610	1164	7924	59	32.00/4.5	-

CRC: Cut Resistance Compound - STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference