



TR 118

Description

TR 118 has been engineered for irrigation machinery. TR 118 features a reinforced carcass and a higher number of lugs, which enable a longer service life.

UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ■ Pivot Irrigator



Version	STANDARD
Tire Type	TL
Tyre size	14.9-24
LI/SS	124;A8

Dimensions US Standard

USA Code	94052363
SW (US) (in)	15.0
OD (US) (in)	49.8
SLR (US) (in)	22.3
RC (US) (in)	147.3
Rim Rec	W 13
Rim Alt	W 12; W 11
ECE	E11-106R-004420
TRA Code	R1

Load Capacity (US)

mph / psi	26	34
25	3520	---
CREEP	---	7440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..