



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 412



PRODUCT DATA SHEET

# EARTHMAX SR 412

RADIAL OTR TIRES



EARTHMAX SR 412 (E-4/L-4) is an All Steel radial tire specially designed for Articulated Dump Trucks, Loaders and Dozers. The unique E-4 deep tread pattern ensures excellent traction. Thanks to its strong All Steel casing and belts, EARTHMAX SR 412 can carry heavy loads providing excellent stability as well as best resistance to snags and punctures. EARTHMAX SR 412 features a squared shoulder design that maximizes ground contact for excellent maneuverability.



Radial



**Technologies**



Steel Belted



All Steel

**Performance**



High Puncture Resistance



Steering Control



Traction

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	29.5 R 25	TL	E-4	**	200 B	CRC	252	765	1865	834	5543	54	25.00/3.5	-
	750/65 R 25 (30/65 R 25)	TL	E-4	**	190 B	CRC	229	780	1602	715	4838	55	24.00/3.0	22.00/3.0 ; 25.00/3.0
	750/65 R 25 (30/65 R 25)	TL	E-4/L-4	**/*	190 B/ 202 A2	CRC	229	780	1602	715	4838	55	24.00/3.0	22.00/3.0 ; 25.00/3.0
Ø 29"	800/65 R 29	TL	E-4/L-4	**/*	198 B/ 208 A2	CRC	206	790	1805	825	5490	58	27.00/3.0	24.00/3.5 ; 25.00/3.5
	800/65 R 29	TL	L-4	**	215 A2	CRC	-	790	1805	825	5490	58	27.00/3.0	24.00/3.5 ; 25.00/3.5

**NEWSIZE**

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference