



## COMMANDER (F)



### Description

COMMANDER (F) is a front 3-rib pattern tire - perfect for soil tillage and haulage applications. Its deep tread made of a cut-and-chip resistant compound ensures a longer tire life, together with high load capacity.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ 2WD Tractor

|           |          |
|-----------|----------|
| Version   | STANDARD |
| Tire Type | TT       |
| Tyre size | 6.50-16  |
| LI/SS     | 98;A6    |

## Dimensions IS Standard

|               |                        |
|---------------|------------------------|
| SW (IS) (mm)  | 183                    |
| OD (IS) (mm)  | 770                    |
| SLR (IS) (mm) | 362                    |
| RC (IS) (mm)  | 2332                   |
| Rim Rec       | 4.50 E                 |
| Rim Alt       | 4.00 E; 5.00 F; 5.50 F |
| ECE           | E11-106R-004107        |
| TRA Code      | F2                     |

## Load Capacity (IS)

|            |      |
|------------|------|
| km/h / bar | 4.20 |
| 30         | 750  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..