



AGRIMAX PROHARVEST

Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Harvester

Version	STEEL BELTED
Tire Type	TL
Tyre size	620/70R26
LI/SS	173;D

Dimensions IS Standard

SW (IS) (mm)	620
OD (IS) (mm)	1528
SLR (IS) (mm)	670
RC (IS) (mm)	4590
Rim Rec	DW 21 B
Rim Alt	DW 20 B; DW 23 B
ECE	E11-106R-0011721

Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8
70	2545	2960	3375	3790	4200	4615	5090	5385	5915
from 65 to 40	2795	3250	3705	4160	4615	5070	5590	5915	6500
30	2855	3315	3780	4245	4710	5175	5705	6035	6630
20	2910	3380	3855	4330	4800	5275	5815	6155	6760
10	3075	3575	4080	4580	5080	5580	6150	6510	7150
*Upto 30 Cyc	3175	3690	4210	4725	5240	5760	6350	6720	7380
*Upto 15 Cyc	3790	4405	5025	5640	6260	6875	7580	8020	8810
*Upto 10 Cyc	4155	4830	5505	6180	6860	7535	8305	8790	9655
10HT	2855	3315	3780	4245	4710	5175	5705	6035	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..