



TR 390

Description

TR 390 is an agro-industrial tire suitable for sugar cane trailers and compactors. TR 390 features high load capacity and increased durability. Its "dual bead HD" version is particularly suitable for industrial tractors and transport operations using trailers, whereas its "dual bead HD special" version is ideal for heavy-duty service.

UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ■ Trailer, Industrial & Construction ■
Compactor



Version	STANDARD
Tire Type	TL
Tyre size	23.1-26
LI/SS	149;A8

Dimensions US Standard

USA Code	94005185
SW (US) (in)	23.4
OD (US) (in)	61.4
SLR (US) (in)	27.2
RC (US) (in)	178.9
Rim Rec	DW 20 B
ECE	E4-106R-002317
TRA Code	R3

Load Capacity (US)

mph / psi	24
25	7150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..