



AGRIMAX RT 765



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	240/70R16
LI/SS	104;A8/B

Dimensions US Standard

USA Code	94022014
SW (US) (in)	9.6
OD (US) (in)	29.2
SLR (US) (in)	13.2
RC (US) (in)	85.7
Rim Rec	W 8
Rim Alt	W 8 L; W 9 L
ECE	E4-106R-000609
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
30	940	1080	1230	1390	1550	1710	1850	1980
25	940	1080	1230	1390	1550	1710	1850	1980
20	1000	1160	1320	1500	1660	1830	1980	2130
5 LT	1260	1440	1660	1870	2080	2300	2490	2670
5 HT	1000	1160	1320	1500	1660	1830	1980	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..