



## AW-18

### Description

AW-18 has been designed for trailers and implement machinery employed in soil tillage operations. Its special design with non-directional lugs and a rounded shoulder area avoids crop damages while maneuvering. The tread pattern has been specifically developed to ensure top self-cleaning properties. AW-18 also stands for best driving comfort and reduced fuel consumption.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ Implement Machinery



Version STANDARD

Tire Type TL

Tyre size 11.5/80-15.3

LI/SS

## Dimensions US Standard

USA Code	94064045
SW (US) (in)	11.7
OD (US) (in)	33.3
Rim Rec	9.00
ECE	E11-106R-006020

## Load Capacity (US)

mph / psi	69
5 FR	7500
15 FR	6380
20 FR	6000
25 FR	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..