



## AGRIMAX SPARGO


### Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TL
Tyre size	VF380/90R46
LI/SS	173;D

## Dimensions IS Standard

SW (IS) (mm)	390
OD (IS) (mm)	1852
SLR (IS) (mm)	846
RC (IS) (mm)	5611
Rim Rec	DW 13 A
Rim Alt	W 13 A; DW 12
ECE	E4-106R-000796
TRA Code	R1

## Load Capacity (IS)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2835	3190	3485	3665	3480	3960	4080	4315	4495	4670	4850	5025	5145	5320	5440	5675	5915
From 65 to 40	3120	3510	3835	4030	4225	4355	4485	4745	4940	5135	5330	5525	5655	5850	5980	6240	6500
30	3180	3580	3910	4110	4305	4440	4570	4835	5035	5235	5435	5635	5765	5965	6095	6360	6630
20	3240	3650	3985	4190	4390	4525	4660	4930	5135	5340	5540	5745	5880	6080	6215	6485	6760
10	3430	3860	4215	4430	4645	4790	4930	5215	5430	5645	5860	6075	6220	6435	6575	6860	7150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..