



AGRIMAX TERIS



Description

AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Harvester

Version	STANDARD
Tire Type	TL
Tyre size	620/75R26CHO
LI/SS	166;A8/B

Dimensions IS Standard

SW (IS) (mm)	625
OD (IS) (mm)	1590
SLR (IS) (mm)	730
RC (IS) (mm)	4851
Rim Rec	DW 20 B
ECE	E4-106R-001419

Load Capacity (IS)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2440	2810	3445	3765	4135	4505	4880	5300
40	2440	2810	3445	3765	4135	4505	4880	5300
30	2615	3010	3690	4030	4430	4825	5225	5675
15 Cyc	4025	4635	5685	6210	6825	7435	8050	8745
10 Cyc	4390	5060	6205	6775	7445	8110	8780	9540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..