



FL 630 SUPER

Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Spreader

Version	STANDARD
Tire Type	TL
Tyre size	580/65R22.5
LI/SS	174;D

Dimensions US Standard

USA Code	94073221
SW (US) (in)	22.9
OD (US) (in)	52.2
SLR (US) (in)	23.4
RC (US) (in)	159.8
Rim Rec	AG 18.00
Rim Alt	AG 16.00; AG 17.00; AG 20.00
ECE	E11-106R-008289

Load Capacity (US)

mph / psi	17	23	29	35	41	46	52	58	65	73	80	87
45	4310	5380	6050	7000	7940	8740	9560	10490	11170	11840	12640	13450
40	4730	5910	6650	7680	8720	9600	10490	11530	12270	13010	13890	14770
30	5730	7150	8050	9300	10550	11630	12700	13950	14850	15740	16810	17880
25	6440	8050	9050	10450	11860	13060	14270	15670	16690	17690	18890	20090
15	7470	9350	10520	12150	13780	15180	16580	18220	19380	20550	21950	23350
5	8510	10640	11970	13830	15700	17280	18880	20740	22070	23400	25000	26590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..