



## AGRIMAX RT 945



### Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	380/90R50
LI/SS	151;A8/B

## Dimensions IS Standard

SW (IS) (mm)	380
OD (IS) (mm)	1954
SLR (IS) (mm)	906
RC (IS) (mm)	5900
Rim Rec	W 12
Rim Alt	W 11; W 13
ECE	E4-106R-001487
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8
50	1865	2415	2970	3210	3450	-
40	1865	2415	2970	3210	3450	-
30	2000	2590	3180	3440	3695	-
10	2745	3365	4090	4765	5020	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..