



## EARTHMAX SR 30



### Description

EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

### UM

US Standard

### Construction

 Radial

### Machinery

OTR ■ Rigid Dump Truck

Version CUT RESISTANT COMPOUND

Tire Type TL

Tyre size 23.5R25

LI/SS 185;B

## Dimensions US Standard

USA Code	94026715
OD (US) (in)	63.3
SLR (US) (in)	28.0
RC (US) (in)	188.9
Rim Rec	19.50/2.5
TRA Code	E3/L3

## Load Capacity (US)

mph / psi	58	62	65	69	73	76
30	16500	17100	18200	18700	19800	20400
5	22700	23400	24700	25400	26800	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..