



## BK 6060

### Description

BK 6060 is a both field- and road-oriented tire for trailers and backhoe loaders in transport as well as digging and loading applications. This block pattern tire provides an extended tire life-cycle.

### UM

IS Standard

### Construction

◇◇ Bias

### Machinery

Industrial & Construction ■ Backhoe Loader



Version

INDUSTRIAL

Tire Type

TT

Tyre size

9.00-16

LI/SS

## Dimensions IS Standard

SW (IS) (mm)	265
OD (IS) (mm)	925
SLR (IS) (mm)	432
RC (IS) (mm)	2847
Rim Rec	6.50 H
Rim Alt	6.00 G

## Load Capacity (IS)

km/h / bar	07:25:00																		
30	2300																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..