



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 43



PRODUCT DATA SHEET



Radial



# EARTHMAX SR 43

RADIAL OTR TIRES



**UK** EARTHMAX SR 43 is an All Steel radial tire specially designed for wheel loaders operating in severe rocky conditions, primarily underground mining. The tire delivers excellent performance in load and carry operations in open pit mines, quarries and scrap yards. Its unique tread design offers superior traction and stability. Thanks to its All Steel casing, EARTHMAX SR 43 provides excellent durability, resistance to snags and punctures as well as a long service life.

### Technologies



All Steel

### Performance



Traction



Hard Rocky Surface



Durability



Stability

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	29.5 R 25	TL	L-4	**	216 A2	CRC	-	785	1875	847	5644	61	25.00/3.5	-
	29.5 R 25	TL	L-4	***	221 A2	CRC	-	785	1875	847	5644	61	25.00/3.5	-
Ø 29"	29.5 R 29	TL	L-4	***	223 A2	CRC	-	768	2003	905	6029	62	25.00/3.5	24.00/3.5 ; 26.00/3.5
	875/65 R 29 (35/65 R 29)	TL	L-4	***	228 A2	CRC	-	852	1877	844	5702	61	27.00/3.5	27.00/3.0 ; 28.00/3.5
Ø 33"	35/65 R 33	TL	L-4	**	224 A2	CRC	-	900	2076	957	6412	61	28.00/3.5	-
	35/65 R 33	TL	L-4	***	229 A2	CRC	-	900	2076	957	6412	61	28.00/3.5	-
	35/65 R 33	TL	SH-4	****	-	CRC	-	900	2076	957	6412	61	28.00/3.5	-
	35/65 R 33	TL	E-4/L-4	****/ ***	-	CRC	-	900	2076	957	6412	61	28.00/3.5	-

CRC: Cut Resistant Compound

In case of underground mine application, consult your servicing dealer or BKT representative



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference