



EARTHMAX SR 468



Description

EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation.

EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.

UM

IS Standard

Construction

Machinery

OTR ■ Rigid Dump Truck

Version HEAT RESISTANT COMPOUND

Tire Type TL

Tyre size 37.00R57

LI/SS 249;B

Dimensions IS Standard

OD (IS) (mm)	3425
SLR (IS) (mm)	1520
RC (IS) (mm)	10315
Rim Rec	27.00/6.0
Rim Alt	29.00/6.0
TRA Code	E4

field_1

km/h / bar	06:50:00	07:15:00	07:00:00	07:25:00	07:50:00	08:15:00	08:00:00			
50	48750	50000	51500	53000	54500	56000	58000			

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..