



## TR 117

### Description

TR 117 is ideal for irrigation applications with pivot irrigators. Its specially designed tread pattern provides excellent traction and outstanding self-cleaning properties.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ Pivot Irrigator



Version	STANDARD
Tire Type	TT
Tyre size	13.6-24
LI/SS	119;A6

## Dimensions IS Standard

SW (IS) (mm)	350
OD (IS) (mm)	1187
SLR (IS) (mm)	541
RC (IS) (mm)	3591
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004419
TRA Code	R1

## Load Capacity (IS)

km/h / bar	2.20	2.85
30	1360	---
CREEP	---	2565

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..