



IS standard



GROWING TOGETHER

# TF 9090



PRODUCT DATA SHEET



Bias



## Performance



Steering Control



# TF 9090

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	4.00 - 12	3.00 D	2.50 C	112	530	255	1573	STD	4	TT	60 A6
	4.00 - 12	3.00 D	2.50 C	112	530	255	1573	STD	6	TT	68 A6
Ø 15"	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	140	655	307	1951	STD	4	TT	73 A6
	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	140	655	307	1951	STD	6	TT	82 A6
Ø 16"	4.00 - 16	3.00 D	-	112	630	301	1877	STD	4	TT	69 A6
	5.50 - 16	4.00 E	3.50 D; 4.50 E	150	710	332	2116	STD	6	TT	86 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	SPL	6	TT	88 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	STD	6	TT	88 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	SPL	8	TT	94 A6
	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	170	735	346	2190	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	765	359	2280	STD	6	TT	91 A6
	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	180	765	359	2280	STD	8	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	SPL	6	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	STD	6	TT	98 A6
7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	SPL	8	TT	103 A6	

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;  
SLR = Static Loaded Radius; RC = Rolling Circumference

STD: Standard - SPL: Special



Bias



Performance



Steering Control



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	STD	8	TT	103 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	207	810	379	2414	STD	10	TT	109 A6
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	257	855	398	2548	STD	8	TT	111 A6
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	257	855	398	2548	SPL	10	TT	116 A6
	9.00 - 16	W 8	6.00 F; W 7; W 8 L	257	855	398	2548	STD	10	TT	116 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	SPL	8	TT	115 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	SPL	10	TT	119 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	STD	8	TT	115 A6
	10.00 - 16	W 8	W 8 L	275	900	409	2714	STD	10	TT	119 A6
	11.00 - 16	W 10 L	W 8; W 8 L	320	970	448	2890	SPL	8	TT	118 A6
	11.00 - 16	W 10 L	W 8; W 8 L	320	970	448	2890	STD	8	TL	118 A6
	11.00 - 16	W 10 L	W 8; W 8 L	320	970	448	2890	STD	8	TT	118 A6
Ø 18"	7.50 - 18	5.50 F	-	207	860	404	2562	SPL	6	TT	101 A6
	7.50 - 18	5.50 F	-	207	860	404	2562	STD	6	TT	101 A6
	7.50 - 18	5.50 F	-	207	860	404	2562	SPL	8	TT	106 A6

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Steering Control



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	7.50 - 18	5.50 F	-	207	860	404	2562	STD	8	TT	106 A6
	7.50 - 18	5.50 F	-	207	860	404	2562	STD	10	TT	113 A6
Ø 19"	4.00 - 19	3.00 D	-	115	715	343	2145	STD	4	TT	72 A6
	6.00 - 19	4.50 E	4.00 E; 5.00 F	167	815	386	2445	STD	6	TT	93 A6
Ø 20"	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	SPL	6	TT	103 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	STD	6	TT	103 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	SPL	8	TT	109 A6
	7.50 - 20	5.50 F	5.00 F	205	915	431	2725	STD	8	TT	109 A6

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference