



US standard



GROWING TOGETHER

MINEFORCE



PRODUCT DATA SHEET



Bias

E-4



MINEFORCE

MINEFORCE is a bias ply tire specially designed for haul trucks in mining and quarry operations. The MINEFORCE high performance haul truck tire is BKT's innovative response to rocky, abrasive and harsh mining environments. It has a unique tread design with specially developed tread compounds for hard, rocky and tough mining conditions. Its large contact patch with rigid lugs provides even tread wear and a longer life cycle.

Technologies



Deep Tread



Heavy Duty



Special Compound



Heat Resistance



Strong Casing

Performance



Traction



Cut and Chip Resistance



High Puncture Resistance

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 35"	94069033	24.00 - 35	TL	48	-	CR	E-4	253	86.2	25.8	39.5	255.2	86	1769	17.00/3.5	-
Ø 49"	94070107	27.00 - 49	TL	48	-	STD	E-4	325	106.1	29.1	49.3	314.4	85	2782	19.50/4.0	-
	94069064	27.00 - 49	TL	54	-	STD	E-4	325	106.1	29.1	49.3	314.4	85	2854	19.50/4.0	-
	94074860	27.00 - 49	TL	66	-	CR	E-4	325	106.1	29.1	49.3	314.4	85	2928	19.50/4.0	-

CR: Cut Resistant - STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference