



ARROW

Description

ARROW is suitable for transport applications with trailers. It is a road-oriented tire that provides a better mileage and a longer service life. ARROW has a high load capacity also at high speeds. An HD version made of a special compound is also available for users that require advanced performance.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ■ Trailer



Version	TRACTOR TRAILER
Tire Type	TT
Tyre size	9.00-20
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	270
OD (IS) (mm)	1040
Rim Rec	7.0
Rim Alt	6.5; 7.5

Load Capacity (IS)

km/h / bar	7.25
40	2715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..