



AGRIMAX RT 765



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version STANDARD

Tire Type TL

Tyre size 620/70R42

LI/SS 160;D

Dimensions IS Standard

SW (IS) (mm)	625
OD (IS) (mm)	1935
SLR (IS) (mm)	876
RC (IS) (mm)	5742
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005835
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6											
65	2475	2880	3285	3690	4095	4500											
50	2600	3025	3450	3875	4300	4725											
40	2715	3160	3600	4045	4490	4930											
30	2850	3315	3780	4245	4710	5175											
10 LT	3320	3860	4405	4945	5490	6030											
10 HT	2850	3315	3780	4245	4710	5175											

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..