



## AGRIMAX RT 765



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	620/70R42
LI/SS	166;D

## Dimensions IS Standard

SW (IS) (mm)	625
OD (IS) (mm)	1935
SLR (IS) (mm)	876
RC (IS) (mm)	5801
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005998
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2495	2865	3290	3710	4135	4560	4985	5300
50	2620	3010	3455	3900	4345	4790	5235	5565
40	2730	3135	3600	4065	4530	4995	5460	5805
30	2865	3295	3780	4270	4755	5245	5730	6095
10 LT	3340	3840	4410	4975	5545	6115	6680	7105
10 HT	2865	3295	3780	4270	4755	5245	5730	6095

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..