



BK 308

Description

BK 308 has been specially designed for trailers and utility tractors. It features excellent traction on all surfaces and tread tie bars to reduce tread groove cracking. The strong casing provides excellent durability and puncture resistance whereas the special tread compound ensures a longer service life.

UM

IS Standard

Construction

◇◇ Bias

Machinery

Agriculture ■ Compact Utility Tractor



Version	STANDARD
Tire Type	TT
Tyre size	6.50-20
LI/SS	112;A6

Dimensions IS Standard

SW (IS) (mm)	190
OD (IS) (mm)	865
Rim Rec	5.50 F
Rim Alt	4.00 E; 5.00 F
ECE	E11-106R-003563

Load Capacity (IS)

km/h / bar	4.8
30	1120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..