



US standard



GROWING TOGETHER

STEER FARM



PRODUCT DATA SHEET



Bias



Performance



Steering Control



STEER FARM

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

| | US CODE | Tire size | RIM | | S.W. (In.) | O.D. (In.) | SLR (In.) | RC (In.) | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | Version | PR | Type | LI/SS |
|-------|----------|-----------|--------|------------------------------|---------------|---------------|--------------|-------------|---------------------------|-------------------------|---------|----|------|--------|
| | | | Rec. | Alt. | | | | | | | | | | |
| Ø 14" | 94046218 | 5.20 - 14 | 3.50 D | 4.00 E | 5.3 | 24.6 | 11.6 | 74.8 | 20 | 16 | STD | 6 | TT | 75 A6 |
| Ø 16" | 94030842 | 6.00 - 16 | 4.50 E | 4.00 E; 5 K; 5.00 F | 6.7 | 29.1 | 13.9 | 89.7 | 23 | 26 | STD | 8 | TT | 91 A8 |
| | 94043811 | 6.50 - 16 | 4.50 E | 4.00 E; 5.00 F; 5.50 F | 7.3 | 30.3 | - | - | 24 | 32 | STD | 8 | TT | 90 A8 |
| | 94030859 | 7.50 - 16 | 5.50 F | 5.00 F; 5 K; 6.00 F | 8.1 | 31.7 | 14.9 | 96.5 | 26 | 42 | STD | 8 | TT | 99 A8 |
| | 94065844 | 7.50 - 16 | 5.50 F | 5.00 F; 5 K; 6.00 F | 8.1 | 31.7 | 14.9 | 96.5 | 26 | 42 | STD | 10 | TT | 105 A8 |
| Ø 20" | 94043736 | 6.50 - 20 | 5.50 F | 4.00 E; 5.00 F | 7.7 | 34.6 | 16.5 | 106.3 | 24 | 39 | STD | 8 | TT | 93 A8 |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference