



US standard



GROWING TOGETHER

# RIB 774 (B)



PRODUCT DATA SHEET



Bias



Technologies



Special Compound

Performance



Durability



High Load Capacity



# RIB 774 (B)

RIB 774 (B) is a low-section implement tire. It is ideal for modern farming and suitable for on- and off-the-road applications with implement machinery and trailers. It features great load capacity and a long tire life-cycle. An "HD" version is available for heavy-duty services.

|              | US CODE  | Tire size    | RIM   |      | S.W.<br>(In.) | O.D.<br>(In.) | SLR<br>(In.) | RC<br>(In.) | TREAD DEPTH<br>(32nds) | TIRE WEIGHT<br>(lbs) | Version | PR | Type | LI/SS |        |
|--------------|----------|--------------|-------|------|---------------|---------------|--------------|-------------|------------------------|----------------------|---------|----|------|-------|--------|
|              |          |              | Rec.  | Alt. |               |               |              |             |                        |                      |         |    |      | DW    | FR     |
|              |          |              |       |      |               |               |              |             |                        |                      |         |    |      |       |        |
| <b>Ø 17"</b> | 94010967 | 15.0/55 - 17 | 13.00 | 13   | 15.4          | 33.5          | 14.8         | 98.0        | 13                     | 66                   | STD     | 14 | TL   | -     | 141 A8 |
|              | 94010936 | 15.0/55 - 17 | 13.00 | 13   | 15.4          | 33.5          | 14.8         | 98.0        | 13                     | 65                   | STD     | 10 | TL   | -     | 134 A8 |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling