



## XL GRIP (E3)



### Description

XL GRIP (E-3) is a bias-ply tire for rigid dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

### UM

US Standard

### Construction

⊠ Bias

### Machinery

OTR ■ Rigid Dump Truck

Version	STANDARD
Tire Type	TT
Tyre size	18.00-25
LI/SS	

## Dimensions US Standard

USA Code	94015757
OD (in)	63.6
SLR (in)	29.1
RC (in)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3

## Load Capacity (US)

mph / psi	62	80
30	16100	-
5	-	27600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..