



PL 801

Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ▪ Rotor Rake/ Tedder, Industrial & Construction ▪ Forklift



Version STANDARD

Tire Type TT

Tyre size 21x8-9

LI/SS

Dimensions IS Standard

SW (IS) (mm)	200
OD (IS) (mm)	535
Rim Rec	6.00 E
Rim Alt	7.00 E
ECE	E11-106R-003643

Load Capacity (IS)

km/h / bar	9.00
25 LOAD WHEEL	2535
25 STEER WHEEL	1950
10 OTHER VEHICLES	2535
25 OTHER VEHICLES	1950
STATIC SIDE LOADER	2945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..