



## MAGLIFT

### Description

MAGLIFT has been particularly designed for forklift in industrial and logistic operations. This solid tyre features high load capacity and outstanding comfort. MAGLIFT shows excellent cut and chip resistance resulting in a long tyre life. Its reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim.

### UM

IS Standard

### Construction

◆ Solid

### Machinery

Industrial & Construction ■



Version

STANDARD

Tyre size

27x10-12/8.00"

LI/SS

## Dimensions IS Standard

|         |             |
|---------|-------------|
| SW (mm) | 240         |
| OD (mm) | 677         |
| Rim Rec | 8.00 G - 12 |

## Load Capacity (IS)

|           |      |
|-----------|------|
| mph / psi | 50   |
| 5         | 8550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..