



IS standard



GROWING TOGETHER

FL 637



PRODUCT DATA SHEET



Radial



160



FL 637

FL 637 is a radial flotation tire suitable for spreaders, trailers and tankers. The reinforced bead structure provides enhanced durability and higher load capacity. In addition to excellent flotation features leading to reduced soil compaction, this tire shows outstanding self-cleaning properties. The directional tread design ensures excellent traction and enabling speeds up to 70 km/h.

Technologies



Reinforced Bead



High Speed

Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 17"	520/50 R 17	151 D/148 E	16.00	-	516	952	414	2930	450	STD
Ø 22.5"	560/45 R 22.5	160 D	AG 16.00	-	544	1076	501	3324	525	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index