



US standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

RT 955



PRODUCT DATA SHEET



Radial

R-1

D

154

AGRIMAX RT 955

RADIAL TRACTOR TIRES



🇺🇸 AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

Technologies



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 24"	94042531	210/90 R 24 (8.3 R 24)	107 A8/B	W 7	W 6	8.4	39.8	18.2	119.2	39	65	STD
Ø 28"	94042548	210/95 R 28 (8.3 R 28)	116 A8/B	W 7	W 6	8.4	43.7	20.2	132.4	39	72	STD
Ø 32"	94040018	210/95 R 32 (8.3 R 32)	120 A8/B	W 7	W 6	8.4	47.8	22.5	145.8	39	86	STD
	94026678	230/95 R 32 (9.5 R 32)	128 A8/B	W 7	W 8	9.0	49.3	23.0	150.0	41	100	STD
	94021857	270/95 R 32 (11.2 R 32)	136 A8/B	W 9	W 8 ; W 10	10.8	52.2	24.2	160.5	43	123	STD
Ø 36"	94027477	230/95 R 36 (9.5 R 36)	130 A8/B	W 7	W 8	9.0	53.2	25.2	161.9	41	105	STD
	94067046	270/80 R 36	134 A8/B	W 9	W 8 ; W 10	10.8	53.0	24.8	161.0	43	123	STD
	94027484	270/95 R 36 (11.2 R 36)	139 A8/B	W 9	W 8 ; W 10	10.8	56.2	26.2	170.7	43	133	STD
Ø 38"	94028139	270/95 R 38 (11.2 R 38)	140 A8/B	W 9	W 8 ; W 10	10.8	58.2	27.4	177.6	43	139	STD
Ø 40"	94055210	230/95 R 40 (9.5 R 40)	132 A8/B	W 7	W 8	9.0	57.2	27.2	175.0	41	119	STD
Ø 42"	94028610	230/95 R 42 (9.5 R 42)	133 A8/B	W 7	W 8	9.0	59.3	28.1	180.9	41	121	STD
	94040636	300/85 R 42 (11.2 R 42)	144 A8/B	W 9	W 10 ; W 11	11.6	62.1	29.3	190.9	45	161	STD
Ø 44"	94042760	210/95 R 44 (8.3 R 44)	120 A8/B	W 7	W 6	8.4	59.8	28.4	183.2	39	115	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial

R-1

D

154

Technologies



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 44"	94027415	230/95 R 44 (9.5 R 44)	134 A8/B	W 7	W 8	9.0	61.3	29.1	188.5	41	126	STD
	94028146	270/95 R 44 (11.2 R 44)	142 A8/B	W 9	W 8 ; W 10	10.8	64.3	30.1	196.2	43	159	STD
Ø 46"	94042555	270/95 R 46 (11.2 R 46)	143 A8/B	W 9	W 8 ; W 10	10.8	66.3	31.2	203.5	43	170	STD
	94021871	300/95 R 46 (12.4 R 46)	148 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	11.6	68.4	32.0	209.4	45	185	STD
	94076154	300/95 R 46 (12.4 R 46)	148 D/ 151 A8	W 9	W 10 ; W 11 ; DW 10 ; DW 11	11.6	68.4	32.0	209.4	45	185	STD
	94044726	340/85 R 46 (13.6 R 46)	150 A8/B	W 12	W 11	13.9	68.7	32.5	210.5	46	223	STD
Ø 48"	94021864	230/95 R 48 (9.5 R 48)	136 A8/B	W 7	W 8	9.0	65.2	31.2	200.2	41	136	STD
	94052837	230/95 R 48 (9.5 R 48)	136 D/ 139 A8	W 7	W 8	9.0	65.2	31.2	200.2	41	136	STD
	94021840	270/95 R 48 (11.2 R 48)	144 A8/B	W 9	W 8 ; W 10	10.8	68.2	32.3	210.7	43	171	STD
	94029426	340/85 R 48 (13.6 R 48)	152 A8/B	W 12	W 11	13.9	70.7	33.7	219.4	46	239	STD
	94059287	340/85 R 48 (13.6 R 48)	151 D/ 154 A8	W 12	W 11	13.9	70.7	33.7	219.4	46	241	STD
	Ø 52"	94029747	300/95 R 52 (12.4 R 52)	151 A8/B	W 9	W 10 ; W 11 ; DW 10 ; DW 11	11.6	74.4	35.0	227.3	45	213
Ø 54"	94032839	270/95 R 54 (11.2 R 54)	146 A8/B	W 9	W 8 ; W 10	10.8	74.2	35.2	228.9	43	203	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference