



AGRIMAX RT 600



Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Harvester

Version STANDARD

Tire Type TL

Tyre size 540/65R28

LI/SS 142;D

Dimensions IS Standard

SW (IS) (mm)	530
OD (IS) (mm)	1413
SLR (IS) (mm)	642
RC (IS) (mm)	4202
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-002980

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1485	1750	1990	2230	2440	2650
50	1560	1840	2090	2340	2565	2785
40	1625	1915	2175	2440	2670	2900
30	1710	2015	2290	2565	2810	3050
10 LT	1995	2350	2670	2990	3275	3555
10 HT	1710	2015	2290	2565	2810	3050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..