



## AT 111 HD

### Description

AT 111 HD is suitable for all-terrain sport racing with ATVs. The increased tread depth and the thick sidewall provide extra grip and braking control in addition to extraordinary traction and high-speed control in power slides. AT 111 HD ensures an extended tire life-cycle.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ ATV



Version	STANDARD
Tire Type	TL
Tyre size	AT21x7-10
LI/SS	30;J

## Dimensions US Standard

USA Code	94027019
SW (US) (in)	7.0
OD (US) (in)	21.0
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0006329

## Load Capacity (US)

mph / psi	7
62	235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..