



IS standard



GROWING TOGETHER

# ROCK GRIP (T)



PRODUCT DATA SHEET



Bias



# ROCK GRIP (T)

ROCK GRIP (E-4) best suits on/off trucks in quarries and short-haul mining applications to carry heavy loads. The special tread compound minimizes cuts and punctures on roughest ground conditions. ROCK GRIP (E-4) offers exceptional traction and an extended tire life-cycle.

## Technologies



Deep Tread

## Performance



Cut Resistance



Durability



Hard Rocky Surface



Heavy Duty

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 20"	10.00 - 20	TT	-	18	-	STD	-	280	1090	-	-	31	7.5	7.0
	11.00 - 20	TT	-	18	-	STD	-	300	1135	-	-	34	8.0	7.5
	12.00 - 20	TT	-	20	-	STD	-	315	1172	-	-	34	8.5	8.0
Ø 24"	12.00 - 24	TT	-	18	-	STD	-	315	1265	595	3755	33	8.5	8.0
	12.00 - 24	TT	-	20	-	STD	-	315	1265	595	3755	33	8.5	8.0

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference