



US standard



GROWING TOGETHER

# AGRIMAX

RADIAL TRACTOR TIRES

## RT 945



PRODUCT DATA SHEET



Radial



Technologies



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning



Traction



# AGRIMAX RT 945

RADIAL TRACTOR TIRES

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 30"	94063857	420/90 R 30	147 A8/B	DW13	W 14 L	16.5	59.8	26.9	180.0	63	243	STD
Ø 42"	94038664	320/90 R 42 (12.4 R 42)	139 A8/B	W 10	W 9 ; W 11	12.6	64.7	29.9	194.6	54	218	STD
Ø 46"	94051694	320/90 R 46 (12.4 R 46)	148 D/ 151 A8	W 10	W 9 ; W 11	12.6	68.7	31.9	206.0	54	240	STD
	94044719	320/90 R 46 (12.4 R 46)	146 A8/B	W 10	W 9 ; W 11	12.6	68.7	31.9	206.0	54	241	STD
	94040551	380/90 R 46 (14.9 R 46)	155 A8/B	W 12	W 11 ; W 13	15.0	72.9	34.1	222.4	57	310	STD
Ø 50"	94021833	380/90 R 46 (14.9 R 46)	159 A8/B	W 12	W 11 ; W 13	15.0	72.9	33.8	224.4	57	310	STD
	94037612	320/90 R 50 (12.4 R 50)	150 A8/B	W 10	W 9 ; W 11	12.6	72.7	34.4	221.2	54	263	STD
	94037025	380/90 R 50 (14.9 R 50)	151 A8/B	W 12	W 11 ; W 13	15.0	76.9	35.7	232.3	57	339	STD
Ø 54"	94065479	380/90 R 50 (14.9 R 50)	160 A8/B	W 12	W 11 ; W 13	15.4	76.9	36.3	234.6	57	354	STD
	94037094	320/90 R 54 (12.4 R 54)	156 A8/B	W 10	W 9 ; W 11	12.6	76.7	36.6	237.0	54	278	STD
	94046799	380/90 R 54 (14.9 R 54)	158 A8/B	W 12	W 11 ; W 13	15.0	80.9	37.9	245.4	57	370	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference