



## MINE STAR XL

### Description

MINE STAR XL-S is a bias-ply tire specifically designed for load haul dumps (LHD) in underground loading and hauling operations. The wide tread design with a smooth central part ensures durability, while the deep shoulder design provides excellent traction and heat dissipation. MINE STAR XL-S is made of special tread and sidewall compounds for excellent cut-and-chip resistance. In addition, the heavy-duty carcass provides extraordinary strength and ensures a longer tire life-cycle and reduced machine downtime.



### UM

IS Standard

### Construction

◆ Bias

### Machinery

OTR ■ Load Haul Dump

Version	STANDARD
Tire Type	TL
Tyre size	54x16.00-24
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	405
OD (IS) (mm)	1380
Rim Rec	10.00 W
TRA Code	L4

## Load Capacity (IS)

km/h / bar	10.00
10	12500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..