



AGRIMAX V-FLECTO



AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tyre is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tyres, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tyre. BKT has designed this tyre with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

IS Standard

 Radial

Agriculture ■

STANDARD

TL

VF710/55R34

170;D

undefined IS Standard

708

1659

726

4910

DW 25 B

DW 27 B

E11-106R-0010831

R1W

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2									
70	2675	3110	3600	4040	4475	4910	5460									
from 65 to 40	2940	3420	3960	4440	4920	5400	6000									
30	2995	3485	4035	4525	5015	5505	6120									
20	3055	3555	4115	4615	5115	5615	6240									
10	3230	3760	4355	4880	5410	5940	6600									
*Upto 10 Cyc with front loader	4115	4785	5540	6215	6885	7560	8400									
10HT	2995	3485	4035	4525	5015	5505	6120									

25-02-2026