



US standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 31



PRODUCT DATA SHEET



Radial

E-3/L-3

B

216

# EARTHMAX SR 31

RADIAL OTR TIRES



EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. Its multiple steel belts provide extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. In addition to outstanding riding comfort, EARTHMAX SR 31 features a special tread compound which is particularly cut-and-heat resistant. It provides excellent riding comfort in 'Load and Carry' operations on hard improved surfaces. The radial casing structure also delivers reduced rolling resistance offering significant fuel savings.

### Technologies



All Steel



Block Pattern

### Performance



Comfort



Traction



Cut Resistance



Stability



Durability

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
															Rec.	Alt.
Ø 25"	94060610	20.5 R 25	TL	***	177 B/186 A2	CRC	E-3/L-3	116	58.3	21.3	26.1	175.2	40	517	17.00/2.0	-
	94048434	23.5 R 25	TL	***	185 B/195 A2	CRC	E-3/L-3	137	63.3	24.1	28.0	188.9	43	751	19.50/2.5	-
	94053735	26.5 R 25	TL	***	193 B/202 A2	CRC	E-3/L-3	158	68.6	27.1	30.2	204.7	48	1006	22.00/3.0	-
	94054381	26.5 R 25	TL	**	209 A2	CRC	L-3	-	68.6	27.1	30.2	204.7	48	1039	22.00/3.0	-
	94054398	29.5 R 25	TL	**	216 A2	CRC	L-3	-	73.3	30.1	32.2	218.7	53	1369	25.00/3.5	-
	94053742	29.5 R 25	TL	***	200 B/208 A2	CRC	E-3/L-3	185	73.3	30.1	32.2	218.7	53	1337	25.00/3.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference