



RIDEMAX FL 690



Description

RIDEMAX FL 690 is a radial flotation and transport tire for tank trucks and trailers. The tire is suitable for 75% on-the-road applications. As a response to the increasing demand for high loads in modern agriculture, BKT has designed this steel-belted tire withstanding very heavy loads and increasing the farmer's productivity. The low rolling resistance contributes to better fuel economy.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tanker, Industrial & Construction ■ Trailer

| | |
|-----------|-------------|
| Version | STANDARD |
| Tire Type | TL |
| Tyre size | VF900/65R32 |
| LI/SS | 197;D |

Dimensions US Standard

| | |
|---------------|-----------------|
| USA Code | 94067176 |
| SW (US) (in) | 36.6 |
| OD (US) (in) | 78.2 |
| SLR (US) (in) | 33.0 |
| RC (US) (in) | 231.4 |
| Rim Rec | DW 31 B |
| Rim Alt | DW 30; TW 30 |
| ECE | E11-106R-006917 |

Load Capacity (US)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 |
|-----------|-------|-------|-------|-------|-------|-------|
| 50 | 11090 | 14190 | 17290 | 19600 | 22700 | 25790 |
| 40 | 12200 | 15590 | 18990 | 21540 | 24940 | 28330 |
| 30 | 14270 | 18240 | 22220 | 25200 | 29180 | 33150 |
| 25 | 15720 | 20110 | 24500 | 27790 | 32180 | 36560 |
| 5 | 19990 | 25570 | 31140 | 35320 | 40900 | 46460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..