



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF750/70R44
LI/SS	186;D

## Dimensions US Standard

USA Code	94066926
SW (US) (in)	29.9
OD (US) (in)	85.6
SLR (US) (in)	37.7
RC (US) (in)	253.9
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-006765
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29
45	9530	11060	12590	14300	15830	17350	19060
from 40 to 25	10470	12150	13820	15710	17380	19060	20940
20	10680	12400	14110	16030	17740	19440	21360
12	10890	12640	14380	16340	18090	19830	21780
5	11520	13370	15210	17280	19120	20960	23040
*Upto 5 Cyc with front loader	14660	17010	19360	21990	24340	26690	29320
5 HT	10680	12400	14110	16030	17740	19440	21360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..