



## TR 390 IND

### Description

TR 390 IND is an industrial tire suitable for industrial trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Industrial & Construction ■ Compactor



Version	DUAL BEAD HD
Tire Type	TL
Tyre size	28L-26
LI/SS	168;A8

## Dimensions US Standard

USA Code	94065349
SW (US) (in)	28.1
OD (US) (in)	61.4
SLR (US) (in)	27.2
RC (US) (in)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
TRA Code	R3

## Load Capacity (US)

mph / psi	42
25	12350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..