



IS standard



GROWING TOGETHER

LOADER PLUS



PRODUCT DATA SHEET



Bias



LOADER PLUS

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suites best for loading and dozing operations.

Performance



Ø 25"	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
14.00 - 25	TT	L-3	20	-	STD	-	375	1368	630	4050	26	10.00/1.5	-	
17.5 - 25	TT	L-3	16	-	STD	-	440	1345	622	3980	26	14.00/1.5	-	
17.5 - 25	TL	L-3	16	-	STD	-	440	1345	622	3980	26	14.00/1.5	-	
17.5 - 25	TT	L-3	20	-	DB	-	440	1345	622	3980	26	14.00/1.5	-	
20.5 - 25	TT	L-3	16	-	STD	-	540	1490	685	4410	29	17.00/2.0	-	
20.5 - 25	TL	L-3	16	-	STD	-	540	1490	685	4410	29	17.00/2.0	-	
20.5 - 25	TT	L-3	20	-	STD	-	540	1490	685	4410	29	17.00/2.0	-	
20.5 - 25	TL	L-3	20	-	STD	-	540	1490	685	4410	29	17.00/2.0	-	
23.5 - 25	TT	L-3	16	-	STD	-	610	1640	749	4855	32	19.50/2.5	-	
23.5 - 25	TL	L-3	16	-	STD	-	610	1640	749	4855	32	19.50/2.5	-	
23.5 - 25	TL	L-3	24	-	STD	-	610	1640	749	4855	32	19.50/2.5	-	
23.5 - 25	TT	L-3	20	-	STD	-	610	1640	749	4855	32	19.50/2.5	-	
23.5 - 25	TL	L-3	20	-	STD	-	610	1640	749	4855	32	19.50/2.5	-	
26.5 - 25	TL	L-3	32	-	STD	-	680	1740	796	5150	36	22.00/3.0	-	
26.5 - 25	TL	L-3	28	-	STD	-	680	1740	796	5150	36	22.00/3.0	-	
29.5 - 25	TL	L-3	32	-	STD	-	760	1860	849	5544	39	25.00/3.5	-	
29.5 - 25	TL	L-3	28	-	STD	-	760	1860	849	5544	39	25.00/3.5	-	

STD: Standard - DB: Dual Bead

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference