

EM 939



GROWING TOGETHER

PRODUKTDATABLAD



IS standard

IMPORTÖR FÖR SVERIGE
GRIPEN[®]
WHEELS

036-307500
order@gripenwheels.se
shop.gripenwheels.se
www.gripenwheels.se



Bias


Technologies



Djupt mönster



EM 939

 EM 939 has been specially designed for excavators in road construction applications. It has a deeper tread and a special lug design ensuring an extended tire life-cycle. The special lug design provides excellent traction during on/off road operations. The tire shows best lateral traction as well as self-cleaning features. The unique tread compound offers cut and chip resistance whereas the strong casing provides a long service life.

	Däckdimension	TYP (Slangtyp Slanglöst)	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	FÄLG	
										Rek.	Alt.
Ø 20"	9.00 - 20	TT	16	-	STD	260	1025	-	-	7.0	65;75
	9.00 - 20	TT	18	-	STD	260	1025	-	-	7.0	65;75
	10.00 - 20	TT	18	-	STD	280	1075	-	-	7.5	70;80

STD: Standard



Tolerans: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Lastindex/Hastighetsklass; S.W. = Sektionsbredd; O.D. = Diameter; SLR = Statisk radie; RC = Rullningsomkrets; Rek. = Rekommenderad; Alt. = Alternativa