



IS standard



GROWING TOGETHER

XL GRIP IND3 (ECH)



PRODUCT DATA SHEET





Bias



XL GRIP IND3 (ECH)

XL GRIP (IND-3) is a bias-ply tire for empty container handlers in stacking and lifting applications. The tire features a strong casing, which provides great durability and as well as a high stability in lift mode.

Technologies



Heavy Duty

Performance



Cut and Chip Resistance



Durability



Hard Surfaces



Stability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	12.00 - 24	TT	24	-	IND	320	1250	585	3710	8.5	8.0
Ø 25"	16.00 - 25	TL	28	-	IND	465	1485	682	4395	11.25/2.0	13.00/2.0
	18.00 - 25	TL	32	-	PORT IND	510	1615	739	4780	13.00/2.5	15.00/2.5
	18.00 - 25	TL	40	-	PORT IND	510	1615	739	4780	13.00/2.5	15.00/2.5

IND: Industrial - PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference