



IS standard



GROWING TOGETHER

EARTHMAX SR 47



PRODUCT DATA SHEET



Radial

E-4

B

212

Technologies



All Steel

Performance



Hard Rocky Surface



Stability



Durability



Traction



EARTHMAX SR 47

RADIAL OTR TIRES

EARTHMAX SR 47 (E-4) is an *All Steel* radial tire specially designed for rigid haul trucks operating in conditions requiring maximum rock cut and puncture resistance. The E-4 tread depth and the unique tread design ensure long wear even on long hauls, thus reducing downtime and increasing productivity. Available in standard and cut-resistant compounds.

Ø 33"	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
18.00 R 33	TL	E-4	**	191 B	CRC	168	510	1885	867	5674	64	13.00/2.5	-	
18.00 R 33	TL	E-4	**	191 B	STD	204	510	1885	867	5674	64	13.00/2.5	-	
18.00 R 33	TL	E-4	**	191 B	HRC	228	510	1885	867	5674	64	13.00/2.5	-	
18.00 R 33	TL	E-4	***	195 B	CRC	168	510	1885	867	5674	64	13.00/2.5	-	
18.00 R 33	TL	E-4	***	195 B	STD	204	510	1885	867	5674	64	13.00/2.5	-	
21.00 R 33	TL	E-4	**	200 B	CRC	227	575	2001	918	6113	67	15.00/3.0	-	
21.00 R 33	TL	E-4	**	200 B	STD	270	575	2001	918	6113	67	15.00/3.0	-	
Ø 35"	21.00 R 35	TL	E-4	**	201 B	CRC	261	585	2045	944	6313	68	15.00/3.0	17.00/3.0
21.00 R 35	TL	E-4	**	201 B	STD	305	585	2045	944	6313	68	15.00/3.0	17.00/3.0	
21.00 R 35	TL	E-4	**	201 B	HRC	355	585	2045	944	6313	68	15.00/3.0	17.00/3.0	
24.00 R 35	TL	E-4	**	209 B	CRC	266	670	2181	983	6565	73	17.00/3.5	-	
24.00 R 35	TL	E-4	**	209 B	STD	315	670	2181	983	6565	73	17.00/3.5	-	
24.00 R 35	TL	E-4	***	212 B	CRC	266	670	2181	983	6565	73	17.00/3.5	-	
24.00 R 35	TL	E-4	***	212 B	STD	315	670	2181	983	6565	73	17.00/3.5	-	

CRC: Cut Resistance Compound - HRC: Heat Resistant Compound - STD: Standard

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference