



AGRIMAXFACTOR

Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors perfect for haulage and soil tillage operations. The improved tread design with increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance. AGRIMAXFACTOR's overall advantages are great handling in combination with driving comfort and excellent durability. The exclusive sidewall shows the "E-READY" logo that highlights BKT's commitment to electric mobility.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	710/70R38
LI/SS	171;D

Dimensions US Standard

USA Code	94071159
SW (US) (in)	28.2
OD (US) (in)	77.1
SLR (US) (in)	34.1
RC (US) (in)	228.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-007637
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
40	6380	7330	8410	9490	10580	11660	12750	13560
30	6700	7690	8840	9980	11110	12260	13390	14240
25	6940	7980	9160	10340	11530	12710	13890	14770
20	7340	8430	9680	10920	12170	13410	14670	15600
5 LT	8550	9820	11280	12730	14190	15640	17100	18180
5 HT	7340	8430	9680	10920	12170	13410	14670	15600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..