



PL 801

Description

PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

UM

IS Standard

Construction

Machinery

Agriculture ▪ Rotor Rake/ Tedder, Industrial & Construction ▪ Forklift



Version

STANDARD

Tire Type

TT

Tyre size

8.25-15

LI/SS

Version	STANDARD
Tire Type	TT
Tyre size	8.25-15
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	236
OD (IS) (mm)	854
Rim Rec	6.5
Rim Alt	6.0; 7.0
ECE	E11-106R-003402

field_1

km/h / bar	08:00:00
25 LOAD WHEEL	4225
25 STEER WHEEL	3250
10 OTHER VEHICLES	4225
25 OTHER VEHICLES	3250
STATIC SIDE LOADER	4910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..