



IS standard



GROWING TOGETHER

RM 2002



PRODUCT DATA SHEET



Bias

RM 2002



RM 2002 is suitable for transport operations with trailers and light trucks, both on and off the road. It ensures long durability and top performance along the entire product life-cycle. Its "industrial" version is ideal for pick & carry cranes.

Performance



Durability

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	11.00 - 20	TT	16	-	STD	302	1101	-	-	8.0	7.5 ; 8.5
	11.00 - 20	TT	18	-	STD	302	1101	-	-	8.0	7.5 ; 8.5
	11.00 - 20	TT	18	-	IND	302	1101	-	-	8.0	7.5 ; 8.5
	11.00 - 20	TT	16	-	IND	302	1101	-	-	8.0	7.5 ; 8.5
	12.00 - 20	TT	18	-	STD	315	1145	534	3538	8.5	8.0 ; 9.0

STD: Standard - IND: Industrial



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference