



SNOW - RIDE (B)



Description

SNOW-RIDE is particularly suitable for road applications in winter conditions with skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

UM

IS Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Loader

Version	STANDARD
Tire Type	TL
Tyre size	15.5-25
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	395
OD (IS) (mm)	1280
SLR (IS) (mm)	569
RC (IS) (mm)	3818
Rim Rec	12.00/1.3
TRA Code	L2

Load Capacity (IS)

km/h / bar	4.00
10	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..