



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 55



PRODUCT DATA SHEET



Radial

L-5S

A2

229

EARTHMAX SR 55

RADIAL OTR TIRES



EARTHMAX SR 55 is an All Steel Radial tire specially designed for loaders and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability.

Technologies



Smooth Tire



Extra Deep Tread

Performance



Stability



Durability



Cut Resistance

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 24"	12.00 R 24	TT	L-5S	**	175 A2	CRC	-	305	1274	572	3787	58	8.50/1.3	8.0; 9.0
	12.00 R 24	TL	L-5S	**	175 A2	CRC	-	305	1274	572	3787	58	8.50/1.3	8.0; 9.0
Ø 25"	17.5 R 25	TL	L-5S	**	182 A2	CRC	-	453	1399	630	4211	68	14.00/1.5	-
	17.5 R 25	TL	L-5S	***	188 A2	CRC	-	453	1399	630	4211	68	14.00/1.5	-
	18.00 R 25	TL	L-5S	**	204 A2	CRC	-	513	1667	733	4852	86	13.00/2.5	-
	18.00 R 25	TL	L-5S	***	206 A2	CRC	-	513	1667	733	4852	86	13.00/2.5	-
	20.5 R 25	TL	L-5S	**	193 A2	CRC	-	535	1543	700	4644	74	17.00/2.0	-
	26.5 R 25	TL	L-5S	**	209 A2	CRC	-	690	1786	810	5375	95	22.00/3.0	-
	26.5 R 25	TL	L-5S	***	214 A2	CRC	-	690	1786	810	5375	95	22.00/3.0	-
	29.5 R 25	TL	L-5S	**	216 A2	CRC	-	777	1912	860	5755	104	25.00/3.5	-
Ø 29"	29.5 R 29	TL	L-5S	**	218 A2	CRC	-	775	2009	911	6047	104	25.00/3.5	24.00/3.5; 26.00/3.5
	29.5 R 29	TL	L-5S	***	223 A2	CRC	-	775	2009	911	6047	104	25.00/3.5	24.00/3.5; 26.00/3.5
Ø 33"	35/65 R 33	TL	L-5S	**	224 A2	CRC	-	900	2065	915	6175	99	28.00/3.5	-

CRC: Cut Resistant Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial

L-5S

A2

229

Technologies



Smooth Tire



Extra Deep Tread

Performance



Stability



Durability



Cut Resistance



	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 33"	35/65 R 33	TL	L-5S	***	229 A2	CRC	-	900	2065	915	6175	99	28.00/3.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference