



EARTHMAX SR 468



Description

EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation.

EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.

UM

US Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version	HEAT RESISTANT COMPOUND
Tire Type	TL
Tyre size	37.00R57
LI/SS	249;B

Dimensions US Standard

USA Code	94517633
OD (US) (in)	134.8
SLR (US) (in)	59.8
RC (US) (in)	406.1
Rim Rec	27.00/6.0
Rim Alt	29.00/6.0
TRA Code	E4

Load Capacity (US)

mph / psi	94	98	102	105	109	112	116
30	107500	110000	113500	117000	120000	123500	128000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..